

HiFlux AUTO-LINE® filters are specially designed for automatic filtration of gelatine.



About the AUTO-LINE® Automatic filter

Installed at several of Europe's largest gelatine productions.

Before installation:

Cleaning manual filters regularly, high maintenance costs, downtime in production.

After installation:

Automatic process, increased productivity, minimal maintenance, no production stops.

Facts for the Auto-line® Automatic filter

Complies to the regulations EC1935/2004 and EU 10/2011, as well as the FDA standards. CIP friendly design with respect to the hygienic design recommendations by the European Hygienic Equipment Design Group (EHEDG).

HiFlux Auto-line® Filter has been designed as a compact, selfcleaning filter. The sturdy construction of the filter makes it well suited for applications in which operational reliability and dependability are essential.

Accurate filtration down to 50 micrometers [µm].

FEATURES

- Removes unwanted particles Homogeneous and uniform product. Increased food safety.
- Continuous flow process No production stops.
- Ensures the quality
- Eliminates downtime Optimizing earnings.







Did you know?

One of our customers achieved nonstop production with the Auto-line self-cleaning filter, when switching out the old manual filters. Today they have an automated filtration process with a much higher production output, better quality and a more homogeneous and uniform product. They have also saved 1 hour each day, because they don't have to change the filter bags on the manual filters.

Facts and regulations:

닛T PED (E ISO 9001 FDA

HiFlux Filtration A/S Lundagervej 25a 8722 Hedensted

www.hiflux-filtration.dk info@hiflux.dk

Tel +45 76 74 16 60 VAT no. dk 13 45 74 76



PROFESSIONAL FILTRATION POTATO STARCH

HiFlux AUTO-LINE® filters are specially designed for automatic filtration of water from potato starch production.



About the AUTO-LINE® Automatic filter

Used at several European potato starch manufacturers. The starch is extracted from potatoes and the water in this production is filtered away with the Auto-line filter.

Before installation:

Cleaning manual filters regularly, high maintenance costs, downtime in production.

After installation:

Automatic process, increased productivity, minimal maintenance, no production stops.

Facts for the Auto-line® Automatic filter

Complies to the regulations EC1935/2004 and EU 10/2011, as well as the FDA standards. CIP friendly design with respect to the hygienic design recommendations by the European Hygienic Equipment Design Group (EHEDG).

HiFlux Auto-line® Filter has been designed as a compact, selfcleaning filter. The sturdy construction of the filter makes it well suited for applications in which operational reliability and dependability are essential.

Accurate filtration down to 35 micrometers [µm].

FEATURES

- Removes unwanted particles Homogeneous and uniform product. Increased food safety.
- Continuous flow process No production stops.
- Ensures the quality
- Eliminates downtime Optimizing earnings.







Did you know?

By an automated process, the starch is extracted from potatoes and in this process the water is filtrated away down to 35 micrometers [µm]. One of our customers has achieved a 20% increase in production after switching to the Auto-line self-cleaning filter and reduced maintenance to a minimum.

Facts and regulations:

닛T PED (E ISO 9001 FDA

HiFlux Filtration A/S Lundagervej 25a 8722 Hedensted

www.hiflux-filtration.dk info@hiflux.dk

Tel +45 76 74 16 60 VAT no. dk 13 45 74 76